

[MSDN Home](#) > [MSDN Library](#) > [User Interface Design and Development](#) > [Shell Programmer's Guide](#) > [Advanced Shell Techniques](#) > [Creating a Shell Namespace Extension](#)

Specifying a Namespace Extension's Location

The root of a namespace extension is normally displayed by Microsoft Windows Explorer as a folder in both tree and folder views. For Windows Explorer to display your extension's files and subfolders, you must specify where the root folder is located in the Shell namespace hierarchy. This location is referred to as a *junction point*.

- [Using Virtual Folders as Junction Points](#)
- [Using File System Folders as Junction Points](#)
- [Opening a View of a Namespace Extension](#)

Using Virtual Folders as Junction Points

The simplest way to define an extension's junction point is to make the root folder a subfolder of a system virtual folder. This type of junction point is referred to as a *virtual junction point*. The **Desktop** and **My Computer** folders are the typical locations for virtual junction points, but you can also define a virtual junction point on a remote computer or under the **My Network Places**, **Internet Explorer**, and **Control Panel** folders.

To define a virtual junction point, create a subkey of the key that represents the appropriate virtual folder and name it with the string form of your extension's class identifier (CLSID). The registered CLSID would appear as follows.

```
HKEY_LOCAL_MACHINE
  Software
    Microsoft
      Windows
        CurrentVersion
          Explorer
            Virtual Folder Name
              Namespace
                {Extension CLSID}
```

Virtual Folder Name is one of the registry key names in the following table.

Location	Virtual Folder Name
My Computer	MyComputer
Desktop	Desktop
Control Panel	ControlPanel
My Network Places	NetworkNeighborhood
Entire Network	NetworkNeighborhood\EntireNetwork
Remote Computer	RemoteComputer

Remote extensions must be initialized with [IRemoteComputer](#).

Note You can also define junction points on a per-user basis by registering them in the equivalent location under the **HKEY_CURRENT_USER** key.

Using File System Folders as Junction Points

There are two ways to define file system folders as junction points. The simplest approach is to create a folder in the appropriate location and append a period to the folder's name, followed by the string form of the CLSID of your extension. Only the folder name will be visible in Windows Explorer. The following example creates a junction point with a display name of MyFolder.

```
MyFolder.{Extension CLSID}
```

Alternatively, you can define a conventionally named folder as a junction point by:

- Making the folder read-only.
- Making the folder a system folder by calling [PathMakeSystemFolder](#).
- Placing a hidden Desktop.ini file in the folder that includes the extension's CLSID.

Desktop.ini is a standard text file that can be added to any folder to customize certain aspects of the folder's behavior. For a general discussion of how to use this file, see [Customizing Folders with Desktop.ini](#). To define a folder as a junction point, the [.ShellClassInfo] section of Desktop.ini must contain the extension's CLSID as follows:

```
[.ShellClassInfo]
CLSID={Extension CLSID}
```

Opening a View of a Namespace Extension

When a user browses into a junction point, Windows Explorer automatically creates a view of the root folder. You can also create a view by explicitly launching Explorer.exe with the extension's CLSID as an argument. You can, for instance, use this approach to launch a view of an extension from a shortcut menu or shortcut. For example, to launch a view of MyExtension that includes a tree view, you can use the following command string.

```
%SystemRoot%\Explorer.exe /e,::{MyExtension CLSID}
```

An alternative command string can be used to launch a view of an object within the extension. This feature would be useful, for instance, for an extension that uses a folder view to allow users to view the contents of one of a number of compressed files.

```
%SystemRoot%\Explorer.exe /e,::{MyExtension CLSID},objectname
```

The *objectname* parameter is the name of the object that is to be viewed. Windows Explorer converts the name to its corresponding PIDL and passes the PIDL to the new folder object's [Initialize](#) method.

Note The CLSID string must be preceded by a pair of colons (::) or the command will fail. The slash-e (/e) flag used in the two sample command lines shown previously instructs Windows Explorer to display a tree view. The flag must be separated from the two colons by a comma. If you do not want a tree view, omit the /e flag and the comma.

Contact Us | **E-Mail This Page** | **MSDN Flash Newsletter** | **Legal**

© 2003 Microsoft Corporation. All rights reserved. [Terms of Use](#) [Privacy Statement](#) [Accessibility](#)

[MSDN Home](#) > [MSDN Library](#) > [User Interface Design and Development](#) > [Shell Programmer's Guide](#) > [Advanced Shell Techniques](#) > [Creating a Shell Namespace Extension](#)

Specifying a Namespace Extension's Location

The root of a namespace extension is normally displayed by Microsoft Windows Explorer as a folder in both tree and folder views. For Windows Explorer to display your extension's files and subfolders, you must specify where the root folder is located in the Shell namespace hierarchy. This location is referred to as a *junction point*.

- o [Using Virtual Folders as Junction Points](#)
- o [Using File System Folders as Junction Points](#)
- o [Opening a View of a Namespace Extension](#)

Using Virtual Folders as Junction Points

The simplest way to define an extension's junction point is to make the root folder a subfolder of a system virtual folder. This type of junction point is referred to as a *virtual junction point*. The **Desktop** and **My Computer** folders are the typical locations for virtual junction points, but you can also define a virtual junction point on a remote computer or under the **My Network Places**, **Internet Explorer**, and **Control Panel** folders.

To define a virtual junction point, create a subkey of the key that represents the appropriate virtual folder and name it with the string form of your extension's class identifier (CLSID). The registered CLSID would appear as follows.

```
HKEY_LOCAL_MACHINE
    Software
        Microsoft
            Windows
                CurrentVersion
                    Explorer
                        Virtual Folder Name
                            Namespace
                                {Extension CLSID}
```

Virtual Folder Name is one of the registry key names in the following table.

Location	Virtual Folder Name
My Computer	MyComputer
Desktop	Desktop
Control Panel	ControlPanel
My Network Places	NetworkNeighborhood
Entire Network	NetworkNeighborhood\EntireNetwork
Remote Computer	RemoteComputer

Remote extensions must be initialized with [IRemoteComputer](#).

Note You can also define junction points on a per-user basis by registering them in the equivalent location under the **HKEY_CURRENT_USER** key.

Using File System Folders as Junction Points

There are two ways to define file system folders as junction points. The simplest approach is to create a folder in the appropriate location and append a period to the folder's name, followed by the string form of the CLSID of your extension. Only the folder name will be visible in Windows Explorer. The following example creates a junction point with a display name of MyFolder.

```
MyFolder.{Extension CLSID}
```

Alternatively, you can define a conventionally named folder as a junction point by:

- o Making the folder read-only.
- o Making the folder a system folder by calling [PathMakeSystemFolder](#).
- o Placing a hidden Desktop.ini file in the folder that includes the extension's CLSID.

Desktop.ini is a standard text file that can be added to any folder to customize certain aspects of the folder's behavior. For a general discussion of how to use this file, see [Customizing Folders with Desktop.ini](#). To define a folder as a junction point, the [.ShellClassInfo] section of Desktop.ini must contain the extension's CLSID as follows:

```
[.ShellClassInfo]
CLSID={Extension CLSID}
```

Opening a View of a Namespace Extension

When a user browses into a junction point, Windows Explorer automatically creates a view of the root folder. You can also create a view by explicitly launching Explorer.exe with the extension's CLSID as an argument. You can, for instance, use this approach to launch a view of an extension from a shortcut menu or shortcut. For example, to launch a view of MyExtension that includes a tree view, you can use the following command string.

```
%SystemRoot%\Explorer.exe /e,::{MyExtension CLSID}
```

An alternative command string can be used to launch a view of an object within the extension. This feature would be useful, for instance, for an extension that uses a folder view to allow users to view the contents of one of a number of compressed files.

```
%SystemRoot%\Explorer.exe /e,::{MyExtension CLSID},objectname
```

The *objectname* parameter is the name of the object that is to be viewed. Windows Explorer converts the name to its corresponding PIDL and passes the PIDL to the new folder object's [Initialize](#) method.

Note The CLSID string must be preceded by a pair of colons (::) or the command will fail. The slash-e (/e) flag used in the two sample command lines shown previously instructs Windows Explorer to display a tree view. The flag must be separated from the two colons by a comma. If you do not want a tree view, omit the /e flag and the comma.

Contact Us | **E-Mail This Page** | **MSDN Flash Newsletter** | **Legal**

© 2003 Microsoft Corporation. All rights reserved. [Terms of Use](#) [Privacy Statement](#) [Accessibility](#)

WEST

Print Selection

Help

Clear

Cancel

Print

Print First Page

Select?	Document ID	Section(s)	Page(s)	# Pages to print	Database
<input checked="" type="checkbox"/>	6363400	all	all	* 84	USPT,PGPB,JPAB,EPAB,DWPI
<input checked="" type="checkbox"/>	6356915	all	all	25	USPT,PGPB,JPAB,EPAB,DWPI
<input checked="" type="checkbox"/>	6061695	all	all	20	USPT,PGPB,JPAB,EPAB,DWPI

Note: Print requests for more than 49 pages are denoted by '*' and are in red.

Building

Room

Printer

cpk2



4c32



gbfrptr



Main Menu

Logout

WEST

Freeform Search

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Term:

namespace and (virtual near folder)

Display: **Documents in Display Format:** **Starting with Number** **Generate:** ☐ Hit List ☒ Hit Count ☐ Side by Side ☐ Image

Search

Clear

Help

Logout

Interrupt

Main Menu

Show S Numbers

Edit S Numbers

Preferences

Cases

Search History

DATE: Tuesday, July 01, 2003 [Printable Copy](#) [Create Case](#)

<u>Set Name</u>	<u>Query</u>
-----------------	--------------

side by side

<u>Hit Count</u>	<u>Set Name</u>
------------------	-----------------

result set

DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=OR

<u>L1</u>	namespace and (virtual near folder)
-----------	-------------------------------------

4	<u>L1</u>
---	-----------

END OF SEARCH HISTORY

Search for

add new drive

MSDN Library

GO

Advanced Search